*JSL, 9(6), June 2024: 649– 659*

**Online ISSN: 2456-1495**
**CODEN (USA): JSLOBJ**

JOURNAL OF SCIENTIFIC LETTERS
www.jslsci.com

# SYNTHESIS AND CHARACTERIZATION OF HYBRID ADSORBENTS FOR TOXIC POLLUTANT REMOVAL FROM CONTAMINATED WATER

**Khumukcham Surchandra Singh**
Research Scholar, Sikkim Alpine University, Namchi, Sikkim
**Dr. Rabina Bhujen**
Research Supervisor, Sikkim Alpine University, Namchi, Sikkim

## ABSTRACT

The increasing contamination of water resources by toxic metals, dyes, pharmaceutical residues, pesticides, and other hazardous substances has intensified the need for efficient and sustainable treatment technologies. Hybrid adsorbents have emerged as promising materials because they combine the beneficial properties of different components, including high surface area, structural stability, selective binding sites, and improved adsorption capacity. This paper examines the synthesis, characterization, and potential application of hybrid adsorbents for removing toxic pollutants from contaminated water. It discusses the incorporation of activated carbon, natural clays, biopolymers, metal oxides, silica, and nanomaterials into composite structures. Important characterization techniques, including Fourier-transform infrared spectroscopy, X-ray diffraction, scanning electron microscopy, and surface-area analysis, are considered for establishing material properties and adsorption mechanisms. Factors affecting pollutant removal, such as pH, adsorbent dosage, contact time, temperature, and initial concentration, are also examined. Finally, the paper highlights regeneration, environmental safety, cost-effectiveness, and scale-up challenges associated with practical water-treatment applications.

***Keywords:*** Hybrid adsorbents, toxic pollutants, water treatment, material synthesis, characterization, adsorption capacity, environmental remediation.

**Online ISSN: 2456-1495**
**CODEN (USA): JSLOBJ**

## I. INTRODUCTION

Water contamination represents a major environmental challenge because domestic activities, industrial operations, mining, agricultural practices, and pharmaceutical production introduce diverse pollutants into surface water and groundwater. Toxic metals such as lead, cadmium, chromium, and mercury may persist in aquatic environments and accumulate in living organisms. Organic contaminants, including synthetic dyes, pesticides, and pharmaceutical compounds, may also interfere with aquatic ecosystems and compromise water quality. Conventional treatment methods can remove particular classes of pollutants effectively, but their performance may become limited when contaminants occur at low concentrations, coexist in complex mixtures, or possess different chemical properties. Consequently, the development of versatile and economical treatment materials remains an important research priority.

Adsorption is widely investigated for water purification because it can operate under relatively mild conditions and can be adapted to batch treatment, fixed-bed columns, and integrated treatment systems. Its effectiveness depends on the chemical and physical characteristics of the adsorbent, including accessible surface area, pore structure, surface charge, and the availability of functional groups. Traditional adsorbents, such as activated carbon, clay minerals, and certain natural materials, can offer useful removal performance. Nevertheless, individual materials may exhibit limitations involving selectivity, mechanical strength, regeneration, or affinity for particular pollutants. These limitations have encouraged researchers to develop hybrid adsorbents that combine two or more complementary materials within a single functional structure. Research reviews describe hybrid materials as an important category of water-decontamination materials because their components can be combined through polymer networks, sol–gel processes, layered structures, and other fabrication approaches (Basu et al., 2020).

Hybrid adsorbents may contain carbonaceous materials, metal oxides, silica, clays, biopolymers, or engineered nanomaterials. Each component contributes particular properties to the resulting material. For example, carbon-based components can provide porosity and aromatic surfaces, while metal oxides may introduce chemically active sites for binding specific inorganic contaminants. Biopolymers can support pollutant binding and facilitate the formation of recoverable structures, whereas mineral components can contribute structural rigidity and ion-exchange properties. When these components are appropriately selected and


***E-mail:** editor.jslsci888@gmail.com*

**Online ISSN: 2456-1495**
**CODEN (USA): JSLOBJ**

integrated, the resulting material may provide a more balanced combination of adsorption performance, stability, and handling characteristics than an individual component. However, improved performance cannot be assumed merely because a material is described as a hybrid; it must be demonstrated through appropriate experiments and comparison with its constituent materials.

The synthesis and characterization of hybrid adsorbents therefore require a systematic approach that links material composition, preparation conditions, structural properties, and pollutant-removal performance. Synthesis determines the distribution of active components, pore accessibility, surface chemistry, and mechanical integrity. Characterization techniques provide evidence concerning functional groups, crystallinity, morphology, elemental composition, and porosity. Subsequent adsorption experiments establish how these properties influence removal efficiency under specified operating conditions. The present paper critically discusses synthesis strategies, characterization techniques, adsorption behaviour, and environmental applications of hybrid adsorbents. It also considers the practical requirements that must be addressed before laboratory-scale materials can be adopted in water-treatment systems.

## II. SYNTHESIS STRATEGIES AND DESIGN OF HYBRID ADSORBENTS

Hybrid adsorbents are generally developed by combining materials with complementary chemical, structural, or functional properties. The selection of components should begin with the target pollutant and the characteristics of the contaminated water. For example, an adsorbent intended to remove positively charged metal ions may require negatively charged surface groups or suitable coordination sites, whereas a material designed for anionic pollutants may require positively charged or metal-based active sites under appropriate pH conditions. Organic contaminants may interact with hydrophobic surfaces, aromatic structures, hydrogen-bonding sites, or other functional groups. The design process should therefore consider the pollutant’s charge, molecular structure, solubility, and chemical stability rather than relying solely on surface-area measurements.

One common approach involves incorporating activated carbon or biochar into mineral, polymeric, or metal-oxide structures. Carbonaceous components can provide porous networks and surfaces capable of interacting with various organic molecules. Their performance depends on precursor selection, activation conditions, pore-size distribution, and


***E-mail:* *editor.jslsci888@gmail.com***

**Online ISSN: 2456-1495**
**CODEN (USA): JSLOBJ**

surface chemistry. Combining carbon with clay or metal oxides may introduce additional binding sites or modify the distribution of surface charges. Agricultural residues may also be converted into carbon-rich materials, creating opportunities to use locally available resources. However, the sustainability of these materials must be evaluated across the entire preparation process, including chemical consumption, heating requirements, washing, and waste generation. A low-cost precursor does not necessarily produce an inexpensive adsorbent if extensive activation or purification is required.

Polymer-based hybrids provide another important synthesis route. Natural polymers such as chitosan, cellulose derivatives, and alginate can be combined with inorganic particles or other functional materials to create beads, films, gels, and porous composite structures. Functional groups present in these polymers may participate in metal-ion coordination or interactions with organic pollutants. Inorganic fillers can improve rigidity, influence porosity, and introduce additional active sites. Cross-linking may improve stability in water, although excessive cross-linking can reduce the accessibility of functional groups or slow pollutant diffusion. The synthesis procedure must balance structural integrity with mass transfer and adsorption capacity. The resulting material should also be tested for polymer dissolution, particle shedding, and changes in performance during repeated use.

Metal-oxide and mineral-based hybrids can be prepared through precipitation, sol–gel processing, surface deposition, hydrothermal synthesis, or related techniques. Iron-, aluminium-, titanium-, and other metal-containing phases may provide chemically active surfaces for selected pollutants. Silica and clay minerals can serve as supporting structures, while layered materials may provide ion-exchange sites and accessible interlayer regions. In some systems, a magnetic component is incorporated to facilitate separation of the adsorbent from treated water. Such designs can reduce the need for conventional filtration in specific applications, but magnetic recovery must be verified under realistic operating conditions. Researchers should also evaluate whether the selected synthesis route produces stable particles or leaves behind residual reagents that could contaminate the treated water.

Nanocomposite fabrication offers opportunities to distribute nanoscale active materials across a supporting matrix. A well-designed support may limit aggregation, improve handling, and reduce the risk of releasing free nanoparticles. Nevertheless, nanoparticle size alone does not determine adsorption effectiveness. Aggregation, pore blockage, surface oxidation, and restricted access to active sites may diminish the expected advantages. Hybrid formation can

involve physical mixing, chemical bonding, in situ growth, or encapsulation. The choice depends on compatibility between the components and the intended application. Evidence of successful hybrid formation should be obtained through complementary characterization rather than inferred from the synthesis procedure alone.

Optimization of synthesis conditions is essential for reproducible material development. Variables such as component ratio, reaction temperature, reaction time, pH, cross-linking concentration, and drying method can affect morphology and surface chemistry. A systematic experimental design can help identify which variables influence adsorption performance and whether interactions occur among them. The synthesized hybrid should be compared with its individual components and, where possible, with a simple physical mixture of the same components. These comparisons help establish whether the hybrid structure provides a genuine functional advantage. Ultimately, the most suitable synthesis method is not necessarily the one that produces the highest laboratory adsorption capacity; it is the method that provides reliable performance, manageable production requirements, safe handling, and realistic potential for scale-up.

## III. CHARACTERIZATION TECHNIQUES AND STRUCTURE–PROPERTY RELATIONSHIPS

Characterization establishes whether a synthesized hybrid possesses the intended composition and structural properties. Fourier-transform infrared spectroscopy (FTIR) is frequently used to identify functional groups and investigate possible changes in chemical bonding following hybrid formation or pollutant adsorption. Shifts in absorption bands may indicate changes in the local chemical environment, although they do not independently prove a particular adsorption mechanism. FTIR results should be interpreted alongside pH-dependent adsorption behaviour, elemental analysis, and other relevant evidence. In metal-binding systems, changes associated with oxygen-, nitrogen-, or sulfur-containing groups may support the proposed involvement of those groups, but additional measurements are needed to distinguish coordination from other interactions.

X-ray diffraction (XRD) provides information about crystalline phases, mineral structures, and changes in crystallinity. It can help establish whether an inorganic component retains its expected phase after synthesis and whether new crystalline phases appear during preparation. However, weakly crystalline or amorphous components may not generate strong diffraction

**Online ISSN: 2456-1495**
**CODEN (USA): JSLOBJ**

features. Scanning electron microscopy (SEM) allows researchers to examine surface morphology, particle shape, aggregation, and visible structural changes. Energy-dispersive X-ray spectroscopy (EDS), when available, can provide complementary information about elemental composition and the distribution of selected elements. These methods are useful for comparing the material before and after adsorption, but surface images alone cannot quantify adsorption capacity or establish that all pores are accessible to pollutants.

Surface-area and porosity measurements are particularly important when a hybrid is intended to remove pollutants through pore filling or surface interactions. Gas-adsorption methods can be used to estimate specific surface area and characterize pore structure, subject to the limitations of the selected analytical model and sample preparation. A higher measured surface area may offer more potential adsorption sites, but it does not automatically guarantee superior removal. The chemical affinity of those sites, pore accessibility in water, and the size and charge of the target contaminant also matter. A material with a smaller surface area may perform well when it contains highly selective binding groups, while a highly porous material may exhibit lower practical performance if its pores are inaccessible under aqueous conditions.

Additional analytical techniques can strengthen the interpretation of hybrid structure. Thermogravimetric analysis can evaluate thermal stability and estimate changes associated with organic and inorganic components. X-ray photoelectron spectroscopy can investigate surface elemental composition and chemical states, where available. Zeta-potential measurements can help assess surface charge as a function of pH, while particle-size analysis can provide information relevant to suspension stability and separation. Magnetic measurements may be necessary for magnetic hybrids. No single technique provides a complete description of an adsorbent; a suitable characterization programme combines methods that address composition, morphology, porosity, surface chemistry, and application-specific properties.

The characterization of adsorbents after pollutant exposure is equally important. Changes in functional groups, elemental signals, crystalline phases, or surface morphology can support interpretations of pollutant binding and possible material alteration. For example, the appearance of a target element in post-adsorption EDS measurements may support its association with the adsorbent, but it does not by itself distinguish adsorption from precipitation or other deposition processes. Similarly, changes in surface charge may be


***E-mail:*** ***editor.jslsci888@gmail.com***

consistent with interactions between pollutant species and the surface. These observations should be considered alongside solution chemistry, blank experiments, and controls designed to identify competing removal pathways.

A strong structure–property analysis links characterization results to measured adsorption behaviour without overstating causal conclusions. If a hybrid exhibits higher pollutant uptake than its individual components, researchers should investigate whether this difference is associated with improved pore accessibility, altered surface charge, increased functional-group density, or another identifiable property. Comparisons should use consistent pollutant concentrations, pH, temperature, adsorbent dosage, and contact times. Reporting synthesis yields, washing procedures, particle size, and measurement uncertainty further improves reproducibility. Such evidence enables researchers to distinguish a material that performs well under a single set of conditions from one whose properties are understood well enough to support further development.

## IV. ADSORPTION PERFORMANCE, ENVIRONMENTAL APPLICATIONS, AND PRACTICAL LIMITATIONS

Adsorption performance is influenced by several interconnected operating variables. Solution pH can change the ionization of surface functional groups and the chemical form of the pollutant. It may also affect metal hydrolysis, precipitation, or complex formation, which can complicate the interpretation of apparent removal. Consequently, experiments involving metal ions should include suitable controls to distinguish adsorption from precipitation. Adsorbent dosage determines the number of available binding sites, but increasing dosage does not always increase adsorption capacity expressed per unit mass because sites may remain unused at low pollutant concentrations. Contact time influences the approach to equilibrium, while initial pollutant concentration establishes the concentration gradient driving mass transfer.

Temperature and competing substances also affect adsorption. Depending on the material and pollutant, temperature may alter diffusion, equilibrium, and the strength of surface interactions. In real water, dissolved organic matter and coexisting ions may compete for binding sites or block pore entrances. Ionic strength can influence electrostatic interactions, and changes in water composition may alter the effective charge of the adsorbent. Therefore, performance established using a single-pollutant laboratory solution should not be treated as

**Online ISSN: 2456-1495**
**CODEN (USA): JSLOBJ**

direct evidence of effectiveness in industrial effluent or natural water. Testing should progress from controlled solutions to mixtures and, ultimately, representative water samples.

Hybrid adsorbents have potential applications in the removal of heavy metals, dyes, pesticides, pharmaceutical residues, and selected inorganic anions. Their suitability depends on the target contaminant and the material's surface chemistry. Metal-oxide and mineral-based hybrids may be useful for certain inorganic species, while carbon-containing hybrids may be suitable for organic contaminants through combinations of pore filling and surface interactions. Polymer-supported materials can be advantageous where bead formation, mechanical recovery, or reuse is important. Reviews of hybrid water-treatment materials document a broad range of applications, including the removal of trace elements, radionuclides, dyes, and organic pollutants (Basu et al., 2020). Recent reviews also emphasize the continued development of sustainable adsorbents and nanocomposite materials, while identifying regeneration, process optimization, and real-water testing as important considerations (Abedpour et al., 2023; *Recent advances on sustainable adsorbents*, 2023).

Regeneration and reuse are central to the practical evaluation of an adsorbent. Desorption may be achieved using suitable changes in pH, ionic strength, solvent composition, or other regeneration conditions. The chosen method must recover adsorption capacity without damaging the material or creating a secondary waste stream that is more difficult to manage than the original water. Researchers should measure performance over multiple adsorption–desorption cycles and report mass loss, structural changes, regeneration efficiency, and the fate of concentrated pollutants. A material that retains a high percentage of its initial capacity over repeated cycles may reduce operating costs, but only if regeneration chemicals, energy requirements, and residual waste are also considered.

Environmental safety must be assessed before practical deployment. Hybrid adsorbents containing metal oxides, engineered nanoparticles, or chemical cross-linkers may release constituents under particular water chemistries. Tests should examine leaching, particle shedding, chemical stability, and potential toxicity of both the unused material and the treated water. Spent adsorbents may contain concentrated toxic substances and should not be disposed of without considering the hazards and recovery options. Depending on the contaminant and adsorbent, regeneration, resource recovery, stabilization, or controlled disposal may be necessary. The choice should be based on the characteristics of the spent

**Online ISSN: 2456-1495**
**CODEN (USA): JSLOBJ**

material and applicable environmental requirements.

Scale-up presents additional challenges, including consistent raw-material supply, reproducible synthesis, separation of fine particles, hydraulic resistance, and competition from other water constituents. Batch experiments are useful for initial screening, but column studies are necessary to investigate breakthrough behaviour and practical treatment capacity under continuous flow. Economic assessment should include raw materials, synthesis, washing, drying, transport, regeneration, and waste management. Life-cycle assessment can help identify whether a proposed hybrid provides a genuine environmental advantage over established treatment materials. Thus, successful development requires more than maximizing adsorption capacity: it requires an integrated evaluation of performance, durability, safety, affordability, and operational feasibility.

## V. CONCLUSION

Hybrid adsorbents offer an adaptable approach to the removal of toxic pollutants from contaminated water because they can combine complementary surface, structural, and chemical properties within a single material. Carbonaceous substances, mineral supports, metal oxides, polymers, and nanomaterials can be integrated through different synthesis routes to address particular pollutant-removal requirements. However, the effectiveness of a hybrid depends on component compatibility, preparation conditions, active-site accessibility, and the chemical characteristics of the target pollutant. Hybrid formation alone should not be interpreted as proof of improved performance; comparative experiments are necessary to establish whether the combined material offers a meaningful advantage over its individual constituents.

A systematic characterization programme is essential for understanding the relationship between synthesis, structure, and adsorption behaviour. FTIR, XRD, SEM–EDS, surface-area analysis, thermal analysis, and surface-charge measurements provide complementary information, but their results must be interpreted collectively. Post-adsorption characterization, solution-phase analysis, and appropriate controls are needed to distinguish adsorption from precipitation or other removal mechanisms. Standardized reporting of experimental conditions and uncertainty can improve the reliability and comparability of research findings.

The practical value of hybrid adsorbents also depends on their ability to operate in complex

**Online ISSN: 2456-1495**
**CODEN (USA): JSLOBJ**

water matrices and withstand repeated use. Competitive ions, organic matter, pH variation, and changes in temperature may influence pollutant uptake. Regeneration, leaching, spent-material management, and separation efficiency therefore require the same attention as initial adsorption capacity. Laboratory results should be followed by multicomponent tests, real-water studies, and continuous-flow experiments before conclusions about full-scale suitability are made.

Future research should prioritize sustainable synthesis, low-cost and locally available precursors, safer preparation methods, reproducible manufacturing, and improved recovery of pollutants from spent adsorbents. Greater integration of material characterization with adsorption modelling, toxicity assessment, life-cycle analysis, and techno-economic evaluation will support more informed decisions about treatment applications. Ultimately, hybrid adsorbents are promising candidates for water purification, but their successful implementation will depend on demonstrating not only effective pollutant removal but also long-term stability, environmental safety, and economic feasibility.

## REFERENCES

1. Tanko Danat, Bitrus & Wuana, Raymond & Chahul, Habibat & Iorungwa, Moses. (2016). Review of adsorption isotherms models. Applied Water Science. 16(3) 1-43.
2. Amina, Aichour & Hassina, Zaghouane-Boudiaf. (2020). Synthesis and characterization of hybrid activated bentonite/alginate composite to improve its effective elimination of dyes stuff from wastewater. Applied Water Science. 10(6) 1-13.
3. Radwan, Emad & Abdel Ghafar, Hany & Moursy, Ahmed & Langford, Cooper & Bedair, Ahmed & Achari, Gopal. (2017). Adsorptive removal of hazardous organic water pollutants by humic acid–carbon hybrid materials: kinetics and isotherm study. Desalination and Water Treatment. 80(1) 297-305.
4. El-Baz, Amro & Hendy, Ibrahim & Dohdoh, Ayman & Srour, Mohamed. (2020). Adsorption technique for pollutants removal; current new trends and future challenges – A Review. The Egyptian International Journal of Engineering Sciences and Technology. 32(1) 1-24.
5. Sorour, Mohamed & Hani, Heba & Shaalan, Hayam & ElSayed, Marwa & El-Toukhy, Mahmoud. (2021). Adsorption isotherms and kinetics pertinent to modified

**Online ISSN: 2456-1495**
**CODEN (USA): JSLOBJ**

composite hydrogel adsorbents adopted for heavy metals removal. International Journal of Applied Science and Engineering. 18(5) 1-12.

6. Sahu, Dharini & Pervez, Shamsh & Karbhal, Indrapal & Tamrakar, Aishwaryashri & Mishra, Archi & Verma, Sushant & Deb, Manas & Ghosh, Kallol & Pervez, Yasmeen & Shrivas, Kamlesh & Satnami, Manmohan. (2024). Applications of different adsorbent materials for the removal of organic and inorganic contaminants from water and wastewater – A review. Desalination and Water Treatment. 317(1) 1-24.
7. Naser, Samadi & Hasanzadeh, Reza & Rasad, Mohamad. (2015). Adsorption isotherms, kinetic, and desorption studies on removal of toxic metal ions from aqueous solutions by polymeric adsorbent. Journal of Applied Polymer Science. 20(15) 1-13.
8. J V, Sri & Vashishth, Rahul. (2021). Next-generation adsorbents for heavy metal removal: organic, inorganic, and hybrid materials. Environmental Sciences Europe. 38(1) 1-30.
9. Rajabi, Mostafa & Keihankhadiv, Shadi & Suhas, Dr & Tyagi, Inderjeet & Karri, Rama & Chaudhary, (2022). Comparison and interpretation of isotherm models for the adsorption of dyes, proteins, antibiotics, pesticides and heavy metal ions on different nanomaterials and non-nano materials—a comprehensive review. Journal of Nanostructure in Chemistry. 13(1) 43-65.